



PURITY C FILTER HEAD SYSTEM – EASY HANDLING AND MAXIMUM FLEXIBILITY

One Filter Head System for all applications

By providing various connections and bypass settings BRITA Professional filter heads form the basis for the PURITY C filter cartridge range. Choose between the filter head that enables a variable by-pass setting of 0–70 %, or a filter head with a fixed by-pass setting of 0 % or 30 % (all available with either 3/8" or John Guest connections). This guarantees you an optimum water quality for every application (coffee and espresso machines, vending machines, combi ovens, conventional ovens and coolers).



Your advantages – One filter head concept for all PURITY C cartridges.

- Various head designs for targeted adaptation to individual requirements
- Simple to handle with rapid-change system
- Innovative locking handle for reliable adjustment
- Water inlet and outlet on one filter head side for spacesaving installation
- Integrated flush and bleed valve
- Simple pre-rinsing and bleeding
- Fast and convenient filter exchange without the need for tools
- Water short-cut if cartridge is not inserted

PURITY C Filter Head System

Three simple steps for optimized water



Available with two connections
G3/8" and JG 8 mm

Flush valve with convenient slider mechanism for all 0–70% filter heads

Two minutes for your new water filter



1. To exchange the filter cartridge, rotate the locking handle to divert the water and release the cartridge. Press the flush valve and depressurise the filter. Remove the filter cartridge from the filter head.



2. The filter cartridge can be pivoted by 90° in the wall mounting bracket for removal. Remove the protective cap from the new filter cartridge. Note the next exchange date in the date field on the filter cartridge.



3. Insert the filter cartridge vertically into the filter head and turn the locking handle until you hear it click. Operate the flush valve and rinse the filter system until the filtered water runs clear without bubbles – done!

The food safety of BRITA Professional water filter products is tested and monitored by independent institutes.



** applies to all materials in contact with water

Products	Order number
Filter head 0% ¹ , G3/8"	1002949 (Pack 1)/297177 (Pack 20)*
Filter head 0% ¹ , JG8	1002942 (Pack 1)*/297176 (Pack 20)*
Filter head 30% ² , G3/8"	1002952 (Pack 1)/297175 (Pack 20)*
Filter head 30% ² , JG8	1002945 (Pack 1)*/297174 (Pack 20)*
Filter head 0–70% ³ , G3/8"	1013637 (Pack 1)/1013634 (Pack 20)*
Filter head 0–70% ³ , JG8	1013636 (Pack 1)*/1013633 (Pack 20)*
PURITY C Filter headset III 0–70% (Filter head G3/8", backflow preventer, CH test kit, wall mounted bracket)	1002937
Accessories	
BRITA FlowMeter 10–100A	298900
Backflow preventer G3/8"	1000639 (Pack 3)
Backflow preventer JG8	292068 (Pack 3)*

¹ For combi steamers, ovens and coolers
² For coffee machines and vending machines
³ Can be used flexibly for all applications

* Not available in Switzerland

Products	Diameter	Connection	Length	Order number
Hoses/Connection modules without arc	DN 13	3/4"–3/4"	2.0m	1007721
	DN 8	3/4"–3/8"	2.0m	1007720
	DN 8	3/4"–3/4"	2.0m	1007719
	DN 8	3/4"–3/4"	1.5m	1007716
	DN 8	3/8"–3/8"	1.5m	1007714
	DN 8	3/4"–3/8"	1.5m	1007706
Hoses/Connection modules with arc	DN 13	3/4"–3/4" arc	2.0m	1007725
	DN 8	3/8"–3/4" arc	1.5m	1007724
	DN 8	3/8"–3/8" arc	1.5m	1007722
Arcs	–	3/4" arc	–	315648
	–	3/8" arc	–	1007740
Shut-off valves	–	1"	–	1007741
	–	3/4"	–	1007743
	–	3/8" with integrated backflow preventer	–	1007745
Reducer Kits	–	3/8" female thread – 3/4" male thread	–	1000898
	–	3/4" female thread – 3/8" male thread	–	364600
Inlet hose DN 8 3/8"–3/8" Shut-off valve	DN 8	3/8"–3/8" Shut-off valve incl. backflow preventer	1.5m	1007730
Inlet hose DN 13 3/4"–1" Shut-off valve	DN 13	3/4"–1"	2.0m	1007739
Hose set I Shut-off valve, 3/4"–1"	DN 8	3/4"–3/8" (2x)	2.0m	1007732
Hose set II Shut-off valve, 3/4"–1"	DN 8	3/4"–3/4" (2x)	2.0m	1007734
Hose set III Shut-off valve, 3/4"–1"	DN 13	3/4"–3/4" (1x w. arc)	2.0m	1007735

Only drinking quality water may be used as the water supply for BRITA water filters.

Headquarters
BRITA GmbH
Heinrich-Hertz-Straße 4
D – 65232 Taunusstein

BRITA Water Filter Systems Ltd.
BRITA House
9 Granville Way
Bicester
GB – Oxfordshire OX26 4JT
tel.: +44 (0) 844 742 4990 | fax: +44 (0) 844 742 4902
clientservices@brita.co.uk
www.brita.co.uk

