

# WITH BRITA, I OPTIMISE WATER PROFESSIONALLY

An overview of our products



## Filter management app

Download our free of charge BRITA Professional FilterManager app and get a reminder for your next filter exchange – automatically, wherever you are. For smartphone and tablets.

For more information please visit:  
[www.professional.brita.net/app](http://www.professional.brita.net/app)



## *IntelliBypass*<sup>®</sup> technology

A largely volumetric-flow-independent bypass water percentage ensures constant water quality, also for low flow rates (for small-volume drinks such as espresso).

The *IntelliBypass*<sup>®</sup> supports:

- consistently high water quality
- the best taste by improving the development of the aromas of food and drinks
- secure machine protection and thus the reduction of additional repair costs

# Content

---

## Products

PURITY C Quell ST	4
PURITY Finest C500	6
PURITY Fresh C50	8
PURITY C1000 AC	10

PURITY Quell ST	12
PURITY Finest	14
PURITY Steam	16
PURITY 1200 Clean	18
PURITY 1200 Clean Extra	20

AquaVend Cool	22
Aqua Aroma	24
Aqua Aroma Crema	26

Remote display	28
FlowMeter 10–100 A	30
FlowMeter 100–700 A	31







## Bypass and capacity tables

PURITY C Quell ST	32
PURITY Quell ST	40
PURITY Finest	41
PURITY Finest C500	42
PURITY Steam	43
PURITY 1200 Clean	44
PURITY 1200 Clean Extra	45

## Certifications 46

Only drinking quality water may be used as the water supply for BRITA water filters.

# An overview of our products

Product	PURITY C Quell ST	PURITY Finest C	PURITY Fresh C	PURITY C AC	PURITY Quell ST
Sizes	C50 C150 C300 C500 C1100	C500	C50	C1000	450 600 1200
Capacity/operational life	960 – 11,500l	3,414l	12,000l	10,000l	4,217 –13,187l
Operating position	horizontal and vertical	vertical	horizontal and vertical	horizontal and vertical	horizontal and vertical
Application					
 Coffee	●	●	●		●
 Vending	●	●	●		●
 Combi steamers	●				
 Conventional ovens	●				
 Dishwashers					
 Cooler			●	●	
Page	4	6	8	10	12

PURITY Finest	PURITY Steam	PURITY Clean	PURITY Clean Extra	AquaVend Cool	AquaAroma	AquaAroma Crema
600 1200	450 600 1200	1200	1200			
4,400 – 8,150l	3,680 – 10,800l	12,000l	5,000l	approx. 5,000 l or 6 months	81 – 242l	80 – 220l
vertical	horizontal and vertical	horizontal and vertical	horizontal and vertical			
●					●	●
●					●	●
	●					
	●					
		●	●			
				●		
14	16	18	20	22	24	26

# PURITY C Quell ST

---

## Technology

Decarbonisation

---

The ideal solution for all those who want to fulfil the highest quality expectations.

---



The PURITY C Quell ST, with five different filter sizes, stands for a reliable reduction in carbonate hardness and thus in substances leading to lime-scale deposits. In addition it reduces unwanted taste and aroma elements and particles and thereby ensures optimum product quality and long operational life of the machine. At the same time, the PURITY C Quell ST filters impress with their simple handling and fitting even in tight installation conditions.



PURITY C Quell ST	C50	C150	C300	C500	C1100
Filter head PURITY C 0–70 % with variable bypass					
Capacity <sup>1</sup> with a carbonate hardness of 10°dH Coffee/espresso/vending machines (bypass setting 40 %)	960l	2,408l	4,000l	6,800l	11,500l
Capacity <sup>1</sup> with a carbonate hardness of 10°dH Combi steamers and conventional ovens (bypass setting 10 %)	660l	1,656l	2,750l	4,675l	7,906l
Filter head PURITY C 30 % with fixed bypass					
Capacity <sup>1</sup> with a carbonate hardness of 10°dH	831l	2,086l	3,464l	5,889l	9,960l
Filter head PURITY C 0 % with fixed bypass					
Capacity <sup>1</sup> with a carbonate hardness of 10°dH	600l	1,505l	2,500l	4,250l	7,188l
Comparable capacity according to DIN 18879-1:2007: The comparable capacity is a standardised indicator to facilitate comparison of different filters. The comparable capacity is determined under extreme conditions. Normally the usable capacity in practical operation is clearly higher than the comparable capacity and may vary greatly depending on the usage conditions					
Comparable capacity	435l	1,278l	2,199l	4,125l	8,670l
Max. operating pressure	8.6bar				
Water intake temperature	4–30°C				
Nominal flow	60l/h			100l/h	
Pressure loss at nominal flow	0.25bar			0.5bar	
Dimensions (W/D/H) with filter head	119/108/ 268mm	117/104/ 419mm	125/119/ 466mm	144/144/ 557mm	184/184/ 557mm
Weight (dry/wet)	1.0/1.6kg	1.8/2.8kg	2.8/4.2kg	4.6/6.9kg	7.7/12.5kg
Connections (input/output)	G3/8" or John Guest* 8mm				
Operating position	horizontal and vertical				
Operation	use after inhouse softening units possible				

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

\*Not available in Switzerland

You can find further bypass and capacity information on pages 32–39.

# PURITY Finest C500

---

## Technology

Softening

---

The ideal solution for those who want to offer their consumers a unique espresso experience.

---



PURITY Finest optimised water, with its ideal mineral composition, releases the typical aromas from the ground coffee beans and supports the development of the authentic espresso taste.

In addition, the water ensures a stable crema with a colour and consistency not achieved before, making the espresso and coffee specialities a particular pleasure. At the same time, the PURITY Finest C filter impresses with its simple handling and fitting even in tight installation conditions.





PURITY Finest	C500
Capacity <sup>1</sup> with a total hardness of 10 °dH and 0% bypass <sup>2</sup>	3,414l
Max. operating pressure	8.6bar
Water intake temperature	4–30°C
Flow at 1 bar pressure loss	140l/h
Nominal flow	100l/h
Pressure loss at nominal flow	0.5bar
Dimensions (W/D/H) Filter head with filter cartridge	144/144/557 mm
Weight (dry/wet)	4.6/6.9 kg
Connections (input/output)	G3/8" or John Guest* 8 mm
Operating position	vertical

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

<sup>2</sup> PURITY Finest C500 cartridges must be operated with a bypass setting of 0%.

\* Not available in Switzerland

You can find further bypass and capacity information on page 42.



# PURITY Fresh C50

---

## Technology

Activated carbon filtration

---

Along with the optimised quality of the water, the machine is also protected and a large proportion of the negative influences caused by the properties of the water can be eliminated.

---



The PURITY Fresh C50 was specifically developed for soft water areas with high particle densities. The activated carbon mixture reliably retains these particles from the machine and end product and ensures a clear, fresh taste.



PURITY Fresh	C50
Capacity <sup>1</sup>	12,000l
Max. operating pressure	8.6bar
Water intake temperature	4–30°C
Flow at 1 bar pressure loss	160l/h
Nominal flow	60l/h
Pressure loss at nominal flow	0.25bar
Empty filter cartridge volume	1l
Dimensions (W/D/H) with filter head	119/108/268mm
Weight (dry/wet)	0.7/1.5 kg
Connections (input/output)	G3/8" or John Guest* 8mm
Operating position	horizontal and vertical

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

\*Not available in Switzerland



# PURITY C1000 AC

---

## Technology

Activated carbon filtration

---

The optimum filter medium for water dispensers.

---



The PURITY C1000 AC, with the fine pores in its activated carbon block, filters unwanted taste and aroma elements out of the water, in particular small particles down to 0.5  $\mu\text{m}$  in accordance with NSF standard 42, as well as any contamination caused by the installation



PURITY	C1000 AC
Capacity <sup>1</sup>	10,000l
Max. operating pressure	8.6bar
Water intake temperature	4 –30°C
Operating flow range and associated pressure loss	30–180l/h/0.2–1.4bar
Flow at 1 bar pressure loss	140l/h
Chlorine reduction	DIN EN 14898 Klasse 1 (>90%)
Chlorine reduction	NSF 42 Class I (50%)
Particle retention	NSF 42 Class I (0.5µm)
Dimensions (W/D/H) with filter head	109/93/238mm
Weight (dry/wet)	0.5/1.0kg
Connections (input/output)	G3/8* or John Guest* 8mm
Operating position	horizontal and vertical

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

\*Not available in Switzerland



# PURITY Quell ST

---

## Technology

Decarbonisation

---

The ideal solution for those who want to fulfil the highest quality expectations.

---



The PURITY C Quell ST uses three different filter sizes to provide a reliable reduction in carbonate hardness and thus in substances forming limescale, as well as unwanted taste and aroma elements and particles. As a result, it ensures optimum product quality and the long operational life of machines. The filters in the PURITY Quell ST series are always the right decision if high flow rates are required.



PURITY Quell ST	450	600	1200
Capacity <sup>1</sup> with a carbonate hardness of 10 °dH Coffee/espresso/vending machines (bypass setting 40 %)	4,217l	7,207l	13,187l
Comparable capacity according to DIN 18879-1:2007: The comparable capacity is a standardised indicator to facilitate comparison of different filters. The comparable capacity is determined under extreme conditions. Normally the usable capacity in practical operation is clearly higher than the comparable capacity and may vary greatly depending on the usage conditions.			
Comparable capacity	2,240l	4,420l	7,253l
Max. operating pressure	6.9bar		
Water intake temperature	4–30 °C		
Flow at 1 bar pressure loss	350l/h		
Nominal flow	60l/h	120l/h	
Pressure loss at nominal flow	0.12bar	0.36bar	0.32bar
Dimensions (height/width)	408/249mm	520/249mm	550/288mm
Weight (dry/wet)	10/12kg	12/15kg	18/24kg
Connections (input/output)	G 1"/G 3/4"		
Operating position	horizontal and vertical		
Operation	use after inhouse softening units possible		

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

You can find further bypass and capacity information on page 40.



# PURITY Finest

---

Technology  
Softening

---

The ideal solution for those who want to offer their consumers a unique espresso experience.

---



PURITY Finest optimised water, with its ideal mineral composition, releases the typical aromas from the ground coffee beans and thus supports the development of the authentic espresso taste. In addition, the water ensures a stable crema with a colour and consistency not achieved before, making espresso and coffee specialities a particular pleasure. The filters in the PURITY Finest series are always the right decision if high flow rates are required.





<b>PURITY Finest</b>	<b>600</b>	<b>1200</b>
Capacity <sup>1</sup> with a total hardness of 10 °dH (bypass setting 0% <sup>2</sup> )	4,400l	8,150l
Comparable capacity according to DIN 18879-1:2007: The comparable capacity is a standardised indicator to facilitate comparison of different filters. The comparable capacity is determined under extreme conditions. Normally the usable capacity in practical operation is clearly higher than the comparable capacity and may vary greatly depending on the usage conditions.		
Comparable capacity	3,038l	5,566l
Max. operating pressure	6.9bar	
Water intake temperature	4–30 °C	
Flow at 1 bar pressure loss	350l/h	
Nominal flow	120l/h	
Pressure loss at nominal flow	0.36 bar	0.32 bar
Dimensions (height/width)	520/249 mm	550/288 mm
Weight (dry/wet)	12/15 kg	18/24 kg
Connections (input/output)	G 1"/G 3/4"	
Operating position	vertical	

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

<sup>2</sup> PURITY Finest cartridges must be operated with a bypass setting of 0 %.

You can find further bypass and capacity information on page 41.



# PURITY Steam

---

## Technology

### Decarbonisation

---

The ideal solution for preparing unique dishes in machines that work smoothly and provide the highest performance over a long period. Benefit from the bypass setting specifically adapted for different steamers ensuring improved flow performance.

---



The PURITY Steam with its filter media specifically tailored to the requirements of steam cooking and baking, removes ions that cause limescale from the water as well as chlorine and particles. The result is a partial demineralised water of the highest quality. The machines are protected even longer against limescale deposits.



<b>PURITY Steam</b>	<b>450</b>	<b>600</b>	<b>1200</b>
Capacity <sup>1</sup> with a carbonate hardness of 10 °dH (bypass position 1)	3,680l	5,771l	10,800l
Comparable capacity according to DIN 18879-1:2007: The comparable capacity is a standardised indicator to facilitate comparison of different filters. The comparable capacity is determined under extreme conditions. Normally the usable capacity in practical operation is clearly higher than the comparable capacity and may vary greatly depending on the usage conditions.			
Comparable capacity	2,754l	4,734l	9,521l
Bypass setting	Position 0: All devices in areas with an extremely high water hardness level (KH ≥ 22 °dH) Position 1: Combi ovens and conventional ovens with direct injection system Position 2: Combi ovens and conventional ovens with boiler system Position 3: All devices in soft water areas (KH ≤ 7 °dH)		
Max. operating pressure	6.9bar		
Water intake temperature	4–30 °C		
Flow at 1 bar pressure loss	500l/h		
Nominal flow	120l/h		
Pressure loss at nominal flow	0.36bar		
Dimensions (height/width)	408/249mm	520/249mm	550/288mm
Weight (dry/wet)	10/12 kg	12/15 kg	18/24 kg
Connections (input/output)	G 1"/G3/4"		
Operating position	horizontal and vertical		
Operation	use after inhouse softening units possible		

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

You can find further bypass and capacity information on page 43.



# PURITY 1200 Clean

---

## Technology

Partial demineralisation

---

The ideal solution for professional washing of cutlery, glass and crockery directly at the bar. For feed water with high carbonate hardness and unproblematic additional mineral content.

---



The PURITY 1200 Clean removes the ions that cause limescale and particles from the feed water in a targeted way. The result is partially demineralised water for ideal washing results.



<b>PURITY Clean</b>	<b>1200</b>
Capacity <sup>1</sup> with a carbonate hardness of 10 °dH (bypass setting 0 %)	12,000l
Max. operating pressure	6 bar
Water intake temperature	4 – 60 °C
Flow at 1 bar pressure loss	850l/h
Nominal flow	300l/h
Pressure loss at nominal flow	0.45 bar
Dimensions (height/width)	550/288 mm
Weight (dry/wet)	18/24 kg
Connections (input/output)	G 1"/G 3/4"
Operating position	horizontal and vertical

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

You can find further bypass and capacity information on page 44.



# PURITY 1200 Clean Extra

---

## Technology

Total demineralisation

---

The ideal solution for the professional washing of high-quality cutlery, superior glasses and fine crockery directly at the bar. For raw water with high carbonate hardness and a high level of additional mineral content.

---



The PURITY 1200 Clean Extra removes particles and ions that cause limescale, marks and streaks from the raw water in a targeted way. The result is total demineralised water for first-class washing results.



<b>PURITY Clean Extra</b>	<b>1200</b>
Capacity <sup>1</sup> with a total hardness of 10 °dH (bypass setting 0 %)	5,000 l
Max. operating pressure	6 bar
Water intake temperature	4–60 °C
Flow at 1 bar pressure loss	850 l/h
Nominal flow	300 l/h
Pressure loss at nominal flow	0.45 bar
Dimensions (height/width)	550/288 mm
Weight (dry/wet)	18/24 kg
Connections (input/output)	G 1"/G 3/4"
Operating position	horizontal and vertical

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

You can find further bypass and capacity information on page 45.



# AquaVend Cool

---

## Technology

Activated carbon filtration for cold-water applications

---

Activated carbon filters for reliable reduction of all unwanted taste and aroma elements.

---



The activated carbon fibre filter provides consistently high water quality, independent of the local conditions. It also retains particles and thus provides perfect protection for the machine.





<b>AquaVend Cool</b>	
Capacity <sup>1</sup> /operational life	5,000l or 6 months
Filter cartridge dimensions (W/D/H)	68/68/162 mm
Complete system dimensions (W/D/H) without head attachments	69/69/191 mm
Installation dimensions (W/D/H)	69/69/215 mm
Operating pressure	2–8 bar
Water intake temperature	4 –30°C
Particle filtration	>0.5µm

<sup>1</sup> The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



# AquaAroma

---

## Technology

Decarbonisation



---

Cartridge for use in coffee machines with Tank Fill system (gravity operation).

---

AquaAroma filter cartridges are suitable for use directly in the water tank in a specially designed or retro-fitted tank system, and for mobile coffee machines with an integrated water tank.



AquaAroma	
Cartridge cup diameter	89.6 mm
Height cartridge cup	36.2 mm
Water intake temperature	4–30°C

Typical capacity – taking account of the local carbonate hardness			
Carbonate hardness °dH	Capacity in litres *	Cups 130 ml	Cups 150 ml
6	242	1,860	1,610
8	181	1,390	1,210
10	145	1,120	970
12	120	930	810
14	103	800	690
16	90	700	600
18	81	620	540

\*The capacities given are standard values that can vary depending on the composition of the feed water. We would be pleased to provide individual recommendations.



# AquaAroma Crema

---

## Technology

Decarbonisation



---

Cartridges for use in coffee machines with an integrated water tank (suction operation).

---

In the AquaAroma Crema filter cartridges, the water is sucked through the cartridge. To fix the cartridge in the tank, no additional brackets are required.

Various adapter solutions for retrofitting as well as a bracket for the cartridge in coffee machines are available.





### AquaAroma Crema

Cartridge cup dimensions (W/D/H)	42.8/106.9/60.8 mm
Water intake temperature	4–30 °C

### Typical capacity – taking account of the local carbonate hardness

Setting Aroma ring	Capacity* in litres	Cups 35 ml	Cups 150 ml
Level A	220	6,300	1,470
Level B	150	4,300	1,000
Level C	80	2,300	540

\*The capacities given are standard values that can vary depending on the composition of the feed water. We would be pleased to provide individual recommendations.



# Remote display

---

---

With the remote display, the customer can see all operating parameters at any time and has more flexibility in the location of the system

---



The remote display set increases the convenience of operation and ensures a better overview of the water filtration. Once mounted and connected to the filter system head, the remote unit remains on the wall with the display attached and offers clarity about consumption, settings and replacement dates.

Remote display	
Remote display (L/W/H)	138/48/103mm
Cable length PURITY remote display	approx. 2 m
Cable length remote display – machine	max. 10 m
Data interface transmission rate	9,600 Baud
Electrical supply	From display unit battery
Switching current	max. 50 m ADC
Degree of protection remote display (only for wall mounting)	IPX 4
Screw size for cover	Torx T6

The remote display can only be used in connection with a filter that is equipped with measurement and display electronics.



# FlowMeter 10–100 A

With the FlowMeter, consumption data and replacement dates can be displayed conveniently at eye level.



The FlowMeter increases the convenience of operation and ensures a better overview of the water filtration. Once installed, the device remains on the filter head and provides clarity about consumption and replacement dates.

## FlowMeter 10–100 A

Display unit (L/W/H) 62/50/17 mm	Sensor (L/W/H) 81.5/43/46 mm
Flow range	10–100l/h
Flow deviation	± 5 %
Operating pressure	max. 8 bar
Pressure loss with flow of 100l/h	< 0.2 bar
Water intake temperature	4–30°C
Ambient temperature operation/storage/transport	0–60°C
Battery	Button cell 3 VDC, type CR2032
Degree of protection display unit (only for wall mounting)	IPX 4
Degree of protection Sensor	IPX 8
Cable length	max. 1.5 m
Inlet connection	G3/8" nut
Outlet connection	G3/8"



# FlowMeter 100–700 A



## FlowMeter 100–700 A

Display unit (L/W/H) 62/50/17 mm	Sensor (L/W/H) 81/43/46 mm
Flow range	100–700l/h
Flow deviation	± max. 5 %
Operating pressure	max. 8bar
Pressure loss with flow of 100l/h	<0.2bar
Water intake temperature	4–30°C
Ambient temperature operation/storage/transport	0–60°C
Battery	Button cell 3 VDC, type CR2032
Degree of protection display unit (only for wall mounting)	IPX 4
Degree of protection Sensor	IPX 8
Cable length	max. 1.5m
Inlet connection	G 3/4" with integrated O-ring washer
Outlet connection	G3/4" nut

# Bypass and capacity tables

PURITY C50 Quell ST filter heads PURITY C 0–70 % with variable bypass

## Coffee/espresso machines and vending machines

Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C50 Quell ST			
		Capacity in litres	Cup 130 ml	Cup 150 ml	Cup 180 ml
4	70	1,900	14,615	12,667	10,556
5	70	1,900	14,615	12,667	10,556
6	70	1,900	14,615	12,667	10,556
7	60	1,821	14,011	12,143	10,119
8	50	1,425	10,962	9,500	7,917
9	50	1,267	9,744	8,444	7,037
10	40	960	7,385	6,400	5,333
11	40	873	6,713	5,818	4,848
12	30	693	5,330	4,619	3,849
13	30	640	4,920	4,264	3,553
14	30	594	4,568	3,959	3,299
15	30	554	4,264	3,695	3,079
16	30	520	3,997	3,464	2,887
17	30	489	3,762	3,261	2,717
18	30	462	3,553	3,079	2,566
19	20	387	2,976	2,579	2,149
20	20	368	2,827	2,450	2,042
21	20	350	2,692	2,333	1,944
22	20	334	2,570	2,227	1,856
23	20	320	2,458	2,130	1,775
24	20	306	2,356	2,042	1,701
25	20	294	2,262	1,960	1,633
26	20	283	2,175	1,885	1,571
27	20	272	2,094	1,815	1,512
28	20	263	2,019	1,750	1,458
29	20	253	1,950	1,690	1,408
30	20	245	1,885	1,633	1,361
31	20	237	1,824	1,581	1,317
32	20	230	1,767	1,531	1,276
33	20	223	1,713	1,485	1,237
34	20	216	1,663	1,441	1,201
35	20	210	1,615	1,400	1,167

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C150 Quell ST filter heads PURITY C 0–70 % with variable bypass

Coffee/espresso machines and vending machines					
Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C150 Quell ST			
		Capacity in litres	Cup 130 ml	Cup 150 ml	Cup 180 ml
4	70	4,766	36,660	31,772	26,477
5	70	4,766	36,660	31,772	26,477
6	70	4,766	36,660	31,772	26,477
7	60	4,569	35,144	30,458	25,382
8	50	3,574	27,495	23,829	19,858
9	50	3,177	24,440	21,181	17,651
10	40	2,408	18,523	16,053	13,378
11	40	2,189	16,839	14,594	12,162
12	30	1,738	13,369	11,586	9,655
13	30	1,604	12,340	10,695	8,912
14	30	1,490	11,459	9,931	8,276
15	30	1,390	10,695	9,269	7,724
16	30	1,303	10,026	8,690	7,241
17	30	1,227	9,437	8,178	6,815
18	30	1,159	8,912	7,724	6,437
19	20	970	7,464	6,469	5,391
20	20	922	7,091	6,145	5,121
21	20	878	6,753	5,853	4,877
22	20	838	6,446	5,587	4,656
23	20	802	6,166	5,344	4,453
24	20	768	5,909	5,121	4,268
25	20	737	5,673	4,916	4,097
26	20	709	5,455	4,727	3,939
27	20	683	5,252	4,552	3,793
28	20	658	5,065	4,390	3,658
29	20	636	4,890	4,238	3,532
30	20	615	4,727	4,097	3,414
31	20	595	4,575	3,965	3,304
32	20	576	4,432	3,841	3,201
33	20	559	4,297	3,724	3,104
34	20	542	4,171	3,615	3,012
35	20	527	4,052	3,512	2,926

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C300 Quell ST filter heads PURITY C 0–70 % with variable bypass

### Coffee/espresso machines and vending machines

Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C300 Quell ST			
		Capacity in litres	Cup 130 ml	Cup 150 ml	Cup 180 ml
4	70	7,917	60,897	52,778	43,981
5	70	7,917	60,897	52,778	43,981
6	70	7,917	60,897	52,778	43,981
7	60	7,589	58,379	50,595	42,163
8	50	5,938	45,673	39,583	32,986
9	50	5,278	40,598	35,185	29,321
10	40	4,000	30,769	26,667	22,222
11	40	3,636	27,972	24,242	20,202
12	30	2,887	22,207	19,246	16,038
13	30	2,665	20,499	17,766	14,805
14	30	2,474	19,035	16,497	13,747
15	30	2,310	17,766	15,397	12,831
16	30	2,165	16,655	14,435	12,029
17	30	2,038	15,676	13,585	11,321
18	30	1,925	14,805	12,831	10,692
19	20	1,612	12,399	10,746	8,955
20	20	1,531	11,779	10,208	8,507
21	20	1,458	11,218	9,722	8,102
22	20	1,392	10,708	9,280	7,734
23	20	1,332	10,242	8,877	7,397
24	20	1,276	9,816	8,507	7,089
25	20	1,225	9,423	8,167	6,806
26	20	1,178	9,061	7,853	6,544
27	20	1,134	8,725	7,562	6,301
28	20	1,094	8,413	7,292	6,076
29	20	1,056	8,123	7,040	5,867
30	20	1,021	7,853	6,806	5,671
31	20	988	7,599	6,586	5,488
32	20	957	7,362	6,380	5,317
33	20	928	7,139	6,187	5,156
34	20	901	6,929	6,005	5,004
35	20	875	6,731	5,833	4,861

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C500 Quell ST filter heads PURITY C 0–70 % with variable bypass

Coffee/espresso machines and vending machines					
Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C500 Quell ST			
		Capacity in litres	Cup 130 ml	Cup 150 ml	Cup 180 ml
4	70	13,458	103,526	89,722	74,769
5	70	13,458	103,526	89,722	74,769
6	70	13,458	103,526	89,722	74,769
7	60	12,902	99,245	86,012	71,677
8	50	10,094	77,644	67,292	56,076
9	50	8,972	69,017	59,815	49,846
10	40	6,800	52,308	45,333	37,778
11	40	6,182	47,552	41,212	34,343
12	30	4,908	37,752	32,718	27,265
13	30	4,530	34,848	30,201	25,168
14	30	4,207	32,359	28,044	23,370
15	30	3,926	30,201	26,175	21,812
16	30	3,681	28,314	24,539	20,449
17	30	3,464	26,648	23,095	19,246
18	30	3,272	25,168	21,812	18,177
19	20	2,740	21,078	18,268	15,223
20	20	2,603	20,024	17,354	14,462
21	20	2,479	19,071	16,528	13,773
22	20	2,366	18,204	15,777	13,147
23	20	2,264	17,412	15,091	12,575
24	20	2,169	16,687	14,462	12,052
25	20	2,083	16,019	13,883	11,569
26	20	2,002	15,403	13,349	11,124
27	20	1,928	14,833	12,855	10,712
28	20	1,859	14,303	12,396	10,330
29	20	1,795	13,810	11,968	9,974
30	20	1,735	13,349	11,569	9,641
31	20	1,679	12,919	11,196	9,330
32	20	1,627	12,515	10,846	9,039
33	20	1,578	12,136	10,518	8,765
34	20	1,531	11,779	10,208	8,507
35	20	1,488	11,442	9,917	8,264

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C1100 Quell ST filter heads PURITY C 0–70 % with variable bypass

### Coffee / espresso machines and vending machines

Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C1100 Quell ST			
		Capacity in litres	Cup 130 ml	Cup 150 ml	Cup 180 ml
4	70	22,760	175,080	151,736	126,447
5	70	22,760	175,080	151,736	126,447
6	70	22,760	175,080	151,736	126,447
7	60	21,819	167,840	145,461	121,218
8	50	17,070	131,310	113,802	94,835
9	50	15,174	116,720	101,157	84,298
10	40	11,500	88,462	76,667	63,889
11	40	10,455	80,420	69,697	58,081
12	30	8,300	63,845	55,332	46,110
13	30	7,661	58,934	51,076	42,563
14	30	7,114	54,724	47,428	39,523
15	30	6,640	51,076	44,266	36,888
16	30	6,225	47,884	41,499	34,583
17	30	5,859	45,067	39,058	32,548
18	30	5,533	42,563	36,888	30,740
19	20	4,634	35,647	30,894	25,745
20	20	4,402	33,864	29,349	24,457
21	20	4,193	32,252	27,951	23,293
22	20	4,002	30,786	26,681	22,234
23	20	3,828	29,447	25,521	21,267
24	20	3,669	28,220	24,457	20,381
25	20	3,522	27,091	23,479	19,566
26	20	3,386	26,049	22,576	18,813
27	20	3,261	25,085	21,740	18,117
28	20	3,145	24,189	20,964	17,470
29	20	3,036	23,355	20,241	16,867
30	20	2,935	22,576	19,566	16,305
31	20	2,840	21,848	18,935	15,779
32	20	2,751	21,165	18,343	15,286
33	20	2,668	20,524	17,787	14,823
34	20	2,590	19,920	17,264	14,387
35	20	2,516	19,351	16,771	13,976

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C Quell ST filter heads PURITY C 0–70 % with variable bypass

Combi steamers / conventional ovens						
Carbonate hardness in °dH	Recommended bypass setting in %	PURITY C50 Quell ST	PURITY C150 Quell ST	PURITY C300 Quell ST	PURITY C500 Quell ST	PURITY C1100 Quell ST
		Capacity in litres				
4	10	1,100	2,759	4,583	7,792	13,177
5	10	1,100	2,759	4,583	7,792	13,177
6	10	1,100	2,759	4,583	7,792	13,177
7	10	943	2,365	3,929	6,679	11,295
8	10	825	2,069	3,438	5,844	9,883
9	10	733	1,839	3,056	5,194	8,785
10	10	660	1,656	2,750	4,675	7,906
11	10	600	1,505	2,500	4,250	7,188
12	10	550	1,380	2,292	3,896	6,589
13	10	508	1,273	2,115	3,596	6,082
14	10	471	1,183	1,964	3,339	5,647
15	10	440	1,104	1,833	3,117	5,271
16	10	413	1,035	1,719	2,922	4,941
17	10	388	974	1,618	2,750	4,651
18	10	367	920	1,528	2,597	4,392
19	10	347	871	1,447	2,461	4,161
20	10	330	828	1,375	2,338	3,953
21	10	314	788	1,310	2,226	3,765
22	10	300	753	1,250	2,125	3,594
23	10	287	720	1,196	2,033	3,438
24	10	275	690	1,146	1,948	3,294
25	10	264	662	1,100	1,870	3,163
26	10	254	637	1,058	1,798	3,041
27	10	244	613	1,019	1,731	2,928
28	10	236	591	982	1,670	2,824
29	10	228	571	948	1,612	2,726
30	10	220	552	917	1,558	2,635
31	10	213	534	887	1,508	2,550
32	10	206	517	859	1,461	2,471
33	10	200	502	833	1,417	2,396
34	10	194	487	809	1,375	2,325
35	10	189	473	786	1,336	2,259

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY C Quell ST filter heads PURITY C with fixed bypass 0 %

Combi steamers / conventional ovens					
Carbonate hardness in °dH	PURITY C50 Quell ST	PURITY C150 Quell ST	PURITY C300 Quell ST	PURITY C500 Quell ST	PURITY C1100 Quell ST
	Capacity in litres				
4	1,000	2,508	4,167	7,083	11,979
5	1,000	2,508	4,167	7,083	11,979
6	1,000	2,508	4,167	7,083	11,979
7	857	2,150	3,571	6,071	10,268
8	750	1,881	3,125	5,313	8,984
9	667	1,672	2,778	4,722	7,986
10	600	1,505	2,500	4,250	7,188
11	545	1,368	2,273	3,864	6,534
12	500	1,254	2,083	3,542	5,990
13	462	1,158	1,923	3,269	5,529
14	429	1,075	1,786	3,036	5,134
15	400	1,003	1,667	2,833	4,792
16	375	941	1,563	2,656	4,492
17	353	885	1,471	2,500	4,228
18	333	836	1,389	2,361	3,993
19	316	792	1,316	2,237	3,783
20	300	753	1,250	2,125	3,594
21	286	717	1,190	2,024	3,423
22	273	684	1,136	1,932	3,267
23	261	654	1,087	1,848	3,125
24	250	627	1,042	1,771	2,995
25	240	602	1,000	1,700	2,875
26	231	579	962	1,635	2,764
27	222	557	926	1,574	2,662
28	214	538	893	1,518	2,567
29	207	519	862	1,466	2,478
30	200	502	833	1,417	2,396
31	194	485	806	1,371	2,319
32	188	470	781	1,328	2,246
33	182	456	758	1,288	2,178
34	176	443	735	1,250	2,114
35	171	430	714	1,214	2,054

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.





## PURITY C Quell ST filter heads PURITY C with fixed bypass 30 %

Coffee /espresso machines and vending machines					
Carbonate hardness in °dH	PURITY C50 Quell ST	PURITY C150 Quell ST	PURITY C300 Quell ST	PURITY C500 Quell ST	PURITY C1100 Quell ST
	Capacity in litres				
4	1,386	3,476	5,774	9,815	16,600
5	1,386	3,476	5,774	9,815	16,600
6	1,386	3,476	5,774	9,815	16,600
7	1,188	2,979	4,949	8,413	14,228
8	1,039	2,607	4,330	7,362	12,450
9	924	2,317	3,849	6,544	11,066
10	831	2,086	3,464	5,889	9,960
11	756	1,896	3,149	5,354	9,054
12	693	1,738	2,887	4,908	8,300
13	640	1,604	2,665	4,530	7,661
14	594	1,490	2,474	4,207	7,114
15	554	1,390	2,310	3,926	6,640
16	520	1,303	2,165	3,681	6,225
17	489	1,227	2,038	3,464	5,859
18	462	1,159	1,925	3,272	5,533
19	438	1,098	1,823	3,100	5,242
20	416	1,043	1,732	2,945	4,980
21	396	993	1,650	2,804	4,743
22	378	948	1,575	2,677	4,527
23	361	907	1,506	2,561	4,330
24	346	869	1,443	2,454	4,150
25	333	834	1,386	2,356	3,984
26	320	802	1,332	2,265	3,831
27	308	772	1,283	2,181	3,689
28	297	745	1,237	2,103	3,557
29	287	719	1,195	2,031	3,434
30	277	695	1,155	1,963	3,320
31	268	673	1,118	1,900	3,213
32	260	652	1,083	1,840	3,112
33	252	632	1,050	1,785	3,018
34	245	613	1,019	1,732	2,929
35	238	596	990	1,683	2,846

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Quell ST

Coffee / espresso machines and vending machines				
Carbonate hardness in °dH	Recommended bypass setting in %	PURITY 450 Quell ST	PURITY 600 Quell ST	PURITY 1200 Quell ST
		Capacity in litres		
4	50	8,250	14,100	25,800
5	50	8,250	14,100	25,800
6	50	8,250	14,100	25,800
7	50	7,071	12,086	22,114
8	50	6,188	10,575	19,350
9	50	5,500	9,400	17,200
10	40	4,217	7,207	13,187
11	40	3,883	6,552	11,988
12	30	3,077	5,260	9,624
13	30	2,841	4,855	8,884
14	30	2,638	4,508	8,249
15	30	2,462	4,208	7,699
16	30	2,308	3,945	7,218
17	30	2,172	3,713	6,793
18	30	2,052	3,506	6,416
19	30	1,944	3,322	6,078
20	20	1,650	2,820	5,160
21	20	1,571	2,686	4,914
22	20	1,500	2,564	4,691
23	20	1,435	2,452	4,487
24	20	1,375	2,350	4,300
25	20	1,320	2,256	4,128
28	20	1,179	2,014	3,686
31	20	1,065	1,819	3,329
35	20	943	1,611	2,949

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Finest

Coffee / espresso machines			
Total hardness in °dH	Recommended bypass setting in %	PURITY Finest 600	PURITY Finest 1200
		Capacity in litres	
4	0	7,333	13,583
5	0	7,333	13,583
6	0	7,333	13,583
7	0	6,286	11,643
8	0	5,500	10,188
9	0	4,889	9,056
10	0	4,400	8,150
11	0	4,000	7,409
12	0	3,667	6,792
13	0	3,385	6,269
14	0	3,143	5,821
15	0	2,933	5,433
16	0	2,750	5,094
17	0	2,588	4,794
18	0	2,444	4,528
19	0	2,316	4,289
20	0	2,200	4,075
21	0	2,095	3,881
22	0	2,000	3,705
23	0	1,913	3,543
24	0	1,833	3,396
25	0	1,760	3,260
26	0	1,692	3,135
27	0	1,630	3,019
28	0	1,571	2,911
29	0	1,517	2,810
30	0	1,467	2,717
31	0	1,419	2,629
32	0	1,375	2,547
33	0	1,333	2,470
34	0	1,294	2,397
35	0	1,257	2,329

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Finest C500

Coffee / espresso machines		
Total hardness in °dH	PURITY Finest C500	
	Recommended bypass setting in %	Capacity in litres
4	0	5,690
5	0	5,690
6	0	5,690
7	0	4,877
8	0	4,268
9	0	3,793
10	0	3,414
11	0	3,104
12	0	2,845
13	0	2,626
14	0	2,439
15	0	2,276
16	0	2,134
17	0	2,008
18	0	1,897
19	0	1,797
20	0	1,707
21	0	1,626
22	0	1,552
23	0	1,484
24	0	1,423
25	0	1,366
26	0	1,313
27	0	1,264
28	0	1,219
29	0	1,177
30	0	1,138
31	0	1,101
32	0	1,067
33	0	1,035
34	0	1,004
35	0	975

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Steam

Combi steamers / conventional ovens									
Carbonate hardness in °dH	PURITY 450 Steam			PURITY 600 Steam			PURITY 1200 Steam		
	Capacity in litres								
	Bypass position			Bypass position			Bypass position		
	0	1/2	3	0	1/2	3	0	1/2	3
4	5,633	6,134	6,760	8,833	9,619	10,600	16,530	17,999	19,836
5	5,633	6,134	6,760	8,833	9,619	10,600	16,530	17,999	19,836
6	5,633	6,134	6,760	8,833	9,619	10,600	16,530	17,999	19,836
7	4,829	5,258	5,794	7,571	8,244	9,086	14,169	15,428	17,002
8	4,225	4,601	5,070	6,625	7,214	7,950	12,398	13,500	14,877
9	3,756	4,089	4,507	5,889	6,412	7,067	11,020	12,000	13,224
10	3,380	3,680	4,056	5,300	5,771	6,360	9,918	10,800	11,902
11	3,073	3,346	3,687	4,818	5,246	5,782	9,016	9,818	10,820
12	2,817	3,067	3,380	4,417	4,809	5,300	8,265	9,000	9,918
13	2,600	2,831	3,120	4,077	4,439	4,892	7,629	8,307	9,155
14	2,414	2,629	2,897	3,786	4,122	4,543	7,084	7,714	8,501
15	2,253	2,454	2,704	3,533	3,847	4,240	6,612	7,200	7,934
16	2,113	2,300	2,535	3,313	3,607	3,975	6,199	6,750	7,439
17	1,988	2,165	2,386	3,118	3,395	3,741	5,834	6,353	7,001
18	1,878	2,045	2,253	2,944	3,206	3,533	5,510	6,000	6,612
19	1,779	1,937	2,135	2,789	3,037	3,347	5,220	5,684	6,264
20	1,690	1,840	2,028	2,650	2,886	3,180	4,959	5,400	5,951
21	1,610	1,753	1,931	2,524	2,748	3,029	4,723	5,143	5,667
23	1,470	1,600	1,763	2,304	2,509	2,765	4,312	4,695	5,175
25	1,352	1,472	1,622	2,120	2,308	2,544	3,967	4,320	4,761
28	1,207	1,314	1,449	1,893	2,061	2,271	3,542	3,857	4,251
31	1,090	1,187	1,308	1,710	1,862	2,052	3,199	3,484	3,839
35	966	1,052	1,159	1,514	1,649	1,817	2,834	3,086	3,400

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Clean

Dishwashers		
Carbonate hardness in °dH	PURITY 1200 Clean	
	Bypass setting 0 %	Bypass setting 10 %
	Capacity in litres	
4	30,000	32,667
5	24,000	26,133
6	20,000	21,778
7	17,143	18,667
8	15,000	16,333
9	13,333	14,519
10	12,000	13,067
11	10,909	11,879
12	10,000	10,889
13	9,231	10,051
14	8,571	9,333
15	8,000	8,711
16	7,500	8,167
17	7,059	7,686
18	6,667	7,259
19	6,316	6,877
20	6,000	6,533
21	5,714	6,222
23	5,217	5,681
25	4,800	5,227
28	4,286	4,667
31	3,871	4,215
35	3,429	3,733

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.



## PURITY Clean Extra

Dishwashers		
Total hardness in °dH	PURITY 1200 Clean Extra	
	Bypass setting 0 %	Bypass setting 10 %
	Capacity in litres	
4	12,500	13,611
5	10,000	10,889
6	8,333	9,074
7	7,143	7,778
8	6,250	6,806
9	5,556	6,049
10	5,000	5,444
11	4,545	4,949
12	4,167	4,537
13	3,846	4,188
14	3,571	3,889
15	3,333	3,630
16	3,125	3,403
17	2,941	3,203
18	2,778	3,025
19	2,632	2,865
20	2,500	2,722
21	2,381	2,593
23	2,174	2,367
25	2,000	2,178
28	1,786	1,944
31	1,613	1,756
35	1,429	1,556

The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

# Certification

---

BRITA Professional strives to have all products certified worldwide. As well as the tests required by law, we also voluntarily subject ourselves to quality checks by independent institutions, with the goal of being able to supply you at all times with products that are a guarantee of safety and quality.



---

Germany  
Safety checked, production monitored:  
test symbol issued by TÜV SÜD Product Service.  
Provides a clear indication of the safety check and  
the monitoring of the production.

# KTW

---

Germany  
“Plastic in drinking water/recommendations”  
ensure that no forbidden substances enter  
the drinking water.



---

Great Britain and Northern Ireland  
Compliance with British Standard 6920 for  
materials in contact with drinking water.



---

Switzerland  
Approval for all point-of-use water filter systems –  
Schweizerischer Verein des Gas- und Wasser-  
faches (Swiss Association for the Gas and Water  
Professions).





#### Denmark

Requirement for approval for products involving drinks and waste-water installations from the ETA – Danish board of European Technical Approval for Construction Products.



#### Russia and CIS countries

Eurasian Customs Union conformity  
Russia/Belarus/Kazakhstan.

# ACS

conform



#### France

Requirement for approval for harmlessness of all plastics and seals used/composition check of all materials used against French positive lists.

#### Norway

Declaration of conformity in accordance with Norwegian production guidelines.

# W

AS/NZS 3497  
LN 600 31  
AGA



#### Australia

AS/NZS 3497-1998 – Australian standard for drinking water treatment devices. Company annual production facility audits.

#### Italy

Declaration of compliance pursuant to Regulation (EC) No 1935/2004 and DM 25/2012 on materials intended to come into contact with food.

### Headquarters

BRITA GmbH

Heinrich-Hertz-Straße 4

D – 65232 Taunusstein

BRITA Water Filter Systems Ltd.

BRITA House

9 Granville Way

Bicester

GB – Oxfordshire OX26 4JT

tel.: +44 (0) 844 742 4990

fax: +44 (0) 844 742 4902

[clientservices@brita.co.uk](mailto:clientservices@brita.co.uk)

[www.brita.co.uk](http://www.brita.co.uk)

